



- Web-Bas Remote Surveillance System
- Motion JPEG Compression
- Aluminum Housing
- PC DVR Software Optional
- Internal Microphone for Audio Transmission
- Mobile Phone Surveillance Software
- 2.4GHz 802.11b Wireless LAN
- Motion Detection and Email Notification
- Standard CS Mount type Lens





Item	KW3701	KW3702	KW3715	KW3716	KW3720
Video Source	¼" CMOS	¼" Sharp CCD		BNC Input	
	AEC, AGC, AWB, ABF, ABLC				
Lens	Standard C/CS Mount 3.6mm/F2.0				
Image Resolution	VGA: 640X480, QVGA: 320X240				
	CIF: 352X288, QCIF: 176X144				
Image Compress	Motion JPEG				
Maximum Frame Rate	100Mbps LAN VGA, QVGA, CIF, QCIF 30fps				
	Adjustable frame rate				
Image Control	Brightness, Contrast, Hue Saturation				
Audio	Internal Microphone (Format: PCM, ADPCM)				RCA Input
Image Record Format	JPG, AVI				
Network Interface	10/100 Mbp RJ-45 Port				
Network Protocol	Web Server, DHCP Client; SMTP, FTP, NTP, ICMP				
	Dynamic DNS Support, PPPoE (A DSL)				
Security	User account management, Motion Detection, Image Recording				
	Event triggered email notification & FTP image upload				
Browser Requirement	Internet explorer 5 or later (ActiveX mode)				
	Netscape 6 or later (Java Mode)				
Software Utility	IPEditV3 (Windows) (Display Camera IP address)				
	Mobile Phone Surveillance software (optional)				
	PC DYR Software (optional)				
Wireless LAN	-----	2.4GHz IEEE 802.11B; 64/128bit WEP Encryption	-----	2.4GHz IEEE 802.11B; 64/128bit WEP Encryption	----
Power	DC 5V/2.5 DC 12V/1.5 ADC 5V/2.5A				
LED	Power Status (red); Network Status (Green and Orange)				
IR Support	External infrared Illuminator Needed				